





UNITED STATES STOVE CO.
271 INDUSTRIAL PARK ROAD
P.O. BOX 151
SOUTH PITTSBURG, TN 37280

WONDERWOOD
AUTOMATIC WOOD BURNING CIRCULATOR

MODEL NO. 2941
2941B
B2941
B2941B

CONTACT LOCAL BUILDING OR FIRE OFFICIALS ABOUT RESTRICTIONS AND INSTALLATION INSPECTION IN YOUR AREA.

MINIMUM CLEARANCES TO COMBUSTIBLE MATERIALS (INCHES)




SIDEWALL BACKWALL INSTALLATION



"PREVENT HOUSE FIRES"

INSTALL AND USE ONLY IN ACCORDANCE WITH THE MANUFACTURER'S INSTALLATION AND OPERATING INSTRUCTIONS AND YOUR LOCAL BUILDING CODES. USE 8 INCH DOWEL BUCK STEEL (4 TOLUENE) CHIMNEY HEATING APPLIANCE OR MASONRY RESIDENTIAL TYPE CHIMNEY. (SPECIAL METHODS ARE REQUIRED WHEN PASSING THROUGH A WALL OR CEILING. SEE INSTRUCTIONS AND LOCAL BUILDING CODES). PREFERRED CHIMNEY: UL 100HT LISTED, ALL FUEL, 6" I.D. INSTALL STOVE A MINIMUM OF 35 INCHES FROM BACKWALL AND 17 INCHES FROM SIDEWALL. CHIMNEY CONNECTOR: MINIMUM 28 INCHES FROM BACKWALL, 25 INCHES TO SIDEWALL AND 24 INCHES FROM CEILING.

FLOOR PROTECTOR (MINIMUM SIZE (INCHES))



DO NOT CONNECT THIS UNIT TO A CHIMNEY SERVING ANOTHER APPLIANCE. DO NOT BUILD FIRE IN HEATER WITHOUT GRATE INSTALLED. OPERATE ONLY WITH DOORS CLOSED. HOT WHILE IN OPERATION. DO NOT TOUCH HEATER OR CHIMNEY. DO NOT CLEAN HEATER, CHIMNEY, OR OTHER COMPONENTS. MAINTAIN A CONSIDERABLE DISTANCE AWAY FROM THE HEATER. DO NOT OBSTRUCT SPACE UNDER HEATER. OPTIONAL BLOWER: US STOVE MODEL CB38.

CAUTION

FOR USE WITH 1/2" OR 3/4" WOOD PELLETS ONLY. DO NOT COVER HEATER OR CHIMNEY CONNECTOR. GLOVES YOU USE TO REMOVE PELLETS FROM HEATER MUST BE CLEAN AND DRY. CLEAN HEATER TWICE MONTHLY AND CLEAN HEATER AND CHIMNEY CONNECTOR TWICE MONTHLY. DO NOT REMOVE OR COVER THIS LABEL. 15994H

FLOOR PROTECTOR MUST BE MADE OF A THERMAL CONDUCTIVITY OF 0.08 BTU IN/HR FT² °F OR LESS. PROTECTOR EXTENDING 18" IN FRONT OF HEATER. DOOR MUST BE CLOSED AND HEATER MUST BE DIRECTLY UNDERNEATH AND 7" TO CHIMNEY CONNECTOR.

TESTED TO UL 297B by **ppp** INTERNATIONAL, Inc. CHIMNEY SYSTEMS, Inc. CHIMNEY NO. 7533-11-11. I.D. DATE: []

EXHIBIT PER METHOD 98A