











U-P. MADE IN U.S.A., 07/18/21 20:52 EXT. 45BR JOHN C

CHARLOTTE PIPE, Inc. TrueFit System 7200 2" PVC TYPE I SCH 40 NSF 304v ASTM D 2665 PVC 1120 PR 280 PSI @ 23°C NSF 304v-G U.P. Code ASTM D 1785-15 CP-110-P MADE IN U.S. 07/18/21 20:52 EXT. 45BR



Richmond
The Water Heater Experts
6 YEAR
LIMITED WARRANTY
ON TANK AND PARTS
FOR RESIDENTS
CALL 1-800-875-8282

INTEGRA
SYSTEM
Flammable Vapor Resistant Technology

ENERGYGUIDE
Estimated Yearly Operating Cost
\$315
258 therms
Estimated Yearly Energy Use

Your cost will depend on your utility rates and use.

WARNING
Flammable Vapor
FIRE AND EXPLOSION HAZARD
Can result in serious injury or death
Do not store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other appliance.

FOR YOUR SAFETY READ BEFORE OPERATING
A WARNING: If you do not follow these instructions and the gas control valve is not properly adjusted, a fire or explosion may result causing property damage, personal injury or death.

FOR YOUR SAFETY READ BEFORE OPERATING
1. The burner has a pilot which is lit by a gas control valve. The gas control valve is located on the front of the burner assembly. The gas control valve is turned on and off by the burner assembly. The burner assembly is located on the front of the burner assembly. The burner assembly is located on the front of the burner assembly.

WARNING
Do not touch the burner assembly when it is hot. The burner assembly is located on the front of the burner assembly. The burner assembly is located on the front of the burner assembly.

**TAKE
TURNS**

CLASS 1 FLEXIBLE AIR DUCT
install confidence