



DO NOT PAINT  
NO PINTAR  
XCEL ENERGY 20454420  
AC-250 MAOP 5 PSI  
150 CFM @ 1/2" DIA.  
ANSI CLASS 250  
TEMP. COMP.  
20454420

8/3/2015



CENTRON<sup>®</sup>

0 015 145 668 100000

F01 01 0000-12 01 0000-12

2 1409

kWh

CL200 240V 3W TYPE C1SC 30TA 1.0Kh

("CAT# 0130511")

Xcel Energy

CA 0.5

FM2S

60Hz



\*1N1057855209

57 855 209

51-0005

**Itron**

WATTHOUR METER

USA

10/08

MILBANK  
TYPE 3A ENCLOSURE

8/3/2015

0177 049720039

0177 049720039

0 1 2 3 4 5 6 7 8 9	0 1 2 3 4 5 6 7 8 9	0 1 2 3 4 5 6 7 8 9	0 1 2 3 4 5 6 7 8 9
PER NET	PER NET	PER NET	PER NET
0 1 2 3 4 5 6 7 8 9	0 1 2 3 4 5 6 7 8 9	<b>TEMP. COMP.</b>	
PER NET	PER NET	<b>CU. FT. AT 60°F</b>	

ETL logo and technical specifications for the meter.

XCEL ENERGY 20454420

**AC-250 MAOP 5 PSI**  
elster  
250 G.P.H. @ 1/2" D.I.P.  
ANSI CLASS 250  
TEMP. COMP.

8/3/2015



Elster



TEMP. COMP.  
CU. FT. AT 60°F

DO NOT PAINT  
NO PINTAR

XCEL ENERGY 20454420

**AC-250 MAOP 5 PSI**  
250 C.F.H. @ 1/2" DIF  
ANSI CLASS 250  
TEMP COMP

20454420

8/3/2015

CENTRON<sup>®</sup>



0 015 145 668 10000  
POLYMER 12 0 000 100

2 1409

kWh

CL200 240V 3W TYPE C1SC 30TA 1.0Kh

("CAT# 0130511")

Xcel Energy

CA 0.5

FM2S

60Hz



\*1N1007653209

57 855 209

51-0005

**Itron**

WATTHOUR METER

USA

10/08

MILBANK  
TYPE 37 ENCLOSURE

8/3/2015