

CITY OF SAINT PAUL

375 Jackson Street., Suite 220 Saint Paul, MN 55101-1806 Telephone: 651-266-8989 Facsimile: 651-266-1919 Web: www.stpaul.gov/dsi

June 26, 2018

Henry Seka PO Box 4622 St Paul MN 55104-0622 US Bank NA 4801 Frederica Street Owensboro KY 42301-0000 Five Brothers Mortgage 12220 E 13 Mile Road #100 Warren MI 48093

Order to Abate Nuisance Building(s)

Dear Sir or Madam:

The Vacant/Nuisance Buildings Unit, Department of the Department of Safety and Inspections, Division of Code Enforcement, hereby declares the premises located at:

993 JAMES AVE

With the following Historic Preservation information: NONE

and legally described as follows, to wit:

Michel Robertsons Addition Lot 23 Blk 8

to comprise a nuisance condition in violation of the Saint Paul Legislative Code, Chapter 45.02, and subject to demolition under authority of Chapter 45.11.

On <u>June 14, 2018</u> a Building Deficiency Inspection Report was compiled and the following conditions were observed.

This list of deficiencies is not necessarily all the deficiencies present at this time. This building(s) is subject to the restrictions of Saint Paul Ordinance Chapter 33.03 and shall not again be used for occupancy until such time as a Certificate of Compliance or a Certificate of Occupancy has been issued. All repairs must be in accordance with appropriate codes. Changes or additions to the electrical system, mechanical system, or the plumbing system may necessitate updating or upgrading the systems involved.

This is a two-story, wood frame, single-family dwelling with a detached, two-stall garage.

The following is excerpted from the December 20, 2013 Code Compliance Report:

BUILDING

- Dry out basement and eliminate source of moisture.
- Remove mold, mildew and moldy or water damaged materials.
- Install handrails (34 inches 38 inches above each nosing) and guardrails (36 inch minimum) at all stairways, and return hand rail ends into a newel post or wall per attachment.
- Repair or Replace any deteriorated window sash, broken glass, sash holders, re-putty, etc as necessary.
- Provide complete storms and screens, in good repair for all door and window openings.
- Weather seal exterior doors, threshold and weather-stripping.
- Install floor covering in bathroom and kitchen that is impervious to water.
- Repair walls, ceiling and floors throughout, as necessary.
- Prepare and paint interior and exterior as necessary. Observe necessary abatement procedures (EPA, MPCA and St. Paul Legislative Code, Chapter 34 for additional information) if lead base paint is present.
- Any framing members that required repair or do not meet code (where wall and ceiling covering is removed, members that are over-spanned, over-spaced, not being carried properly, door and window openings that are not adequately supported, etc.) are to be reconstructed in an approved manner.
- Charred building components shall be scraped or sandblasted completely clean and water-damaged components replaced. A determination of necessary fire damage corrective measures shall be made by this department or by a registered structural engineer as to replacement, repairs, etc. All smoke damaged and charred members shall be cleaned, sealed and deodorized.
- Where wall and ceiling covering is removed install full thickness or code-specified insulation.
- Air-seal and insulate attic/access door.
- Install Smoke Detectors/Carbon Monoxide Detectors per MN Conservation Code and the MN Dept. of Labor and Industry: Install per code where feasible.
- Provide major clean-up of premises.
- Repair siding, soffit, fascia, trim, etc. as necessary.
- Provide proper drainage around house to direct water away from foundation of house.
- Provide proper drainage around house to direct water away from foundation of garage.
- Install downspouts and a complete gutter system.
- Install rain leaders to direct drainage away from foundation.
- Provide general rehabilitation of garage.
- Install address numbers visible from street and on the alley side of garage.
- Provide ground cover capable of controlling sediment and erosion.
- Grade must drain away from foundation of dwelling. Maintain 6 inch clearance between wood and soil.
- Jack up northeast corner of house and repair foundation. Also engineers report required.
- Remove and replace insulation and drywall as needed with inspections for northeast corner lower level bedroom.
- Re-nail sheathing on garage walls and replace siding and soffits where damaged or missing.
- Repair and re-level garage floor and fill in cracks.
- Replace east side sidewalks after foundation repair and re-grading around house.
- Replace rear deck steps to code.

• A building permit is required to correct the above deficiencies.

ELECTRICAL

- Ground the electrical service to the water service with a copper conductor within 5 feet of the entrance point of the water service
- Bond around water meter with a copper wire sized for the electrical service per Article 250 of the NEC
- Properly strap service conduit on the exterior of the house.
- Replace GFCI receptacle in first bathroom adjacent to the sink because it is not operating properly.
- Ground laundry room fluorescent light in basement.
- Remove all cord wiring in garage to lights, or rewire to current NEC.
- Repair or Replace all broken, missing or loose light fixtures, switches and outlets, covers and plates
- Check all outlets for proper polarity and verify ground on 3-prong outlets
- Install hard-wired, battery backup smoke detector and other smoke detectors as required by the IRC. Also, Install carbon monoxide detector(s) within 10 feet of all bedrooms
- Properly wire exterior lights at back door. Install weatherproof box.
- Replace all painted-over receptacles.
- Repair garage feeder conduit on back of house to current NEC.
- All added receptacles must be grounded, tamper-resistant and be on an Arc-Fault Circuit Interrupter-protected circuit.
- Any open walls or walls that are opened as part of this project must be wired to the standards of the current NEC.
- All electrical work must be done by a Minnesota-licensed electrical contractor under an electrical permit.

PLUMBING

- Basement Water Heater not fired or in service.
- Basement Water Meter support meter properly.
- Basement Water Piping add appropriate hangers.
- Basement Gas Piping dryer gas shutoff; connector or piping incorrect.
- Basement Gas Piping run dryer vent to code.
- Basement Soil and Waste Piping no soil stack base clean out
- Basement Laundry Tub provide a vacuum breaker for the spout.
- Basement Lavatory incorrectly vented.
- Basement Lavatory water piping incorrect.
- Basement Tub and Shower provide anti-scald valve.
- Bathroom Plumbing General Caulk all fixtures to code.
- First Floor Toilet Facilities reset the toilet on a firm base.
- First Floor Tub and Shower provide anti-scald valve.
- Exterior Lawn Hydrants Requires backflow assembly or device.
- All the above corrections to waste, vent, water, and gas piping shall be per the Minnesota Plumbing Code Chapter 4715 & Chapter 326, the Minnesota Mechanical Code, the

Minnesota Fuel Gas Code, and the Saint Paul Regional Water Code. All plumbing must be done by a plumbing contractor licensed in the State of Minnesota and the City of St. Paul under an approved permit.

HEATING

- Clean and Orsat test furnace burner. Check all controls for proper operation. Check furnace heat exchanger for leak; provide documentation from a licensed contractor that the heating unit is safe
- Provide support for gas lines to code
- Plug, cap and/or remove all disconnected gas lines
- Verify that basement bathroom exhaust is run to the outside in a code compliant manner. Replace exterior termination cover.
- All supply and return ducts for warm air heating system must be clean before final approval for occupancy. Provide documentation from a licensed duct-cleaning contractor that the duct system has been cleaned.
- Repair and/or replace heating registers as necessary
- Provide heat in every habitable room and bathrooms
- Run condensate drain three-quarter inch nominal size from A/C unit coil in basement to an approved location.
- Provide a means of returning air from every habitable room to the furnace. Return air cannot be taken from closets, bathrooms, toilet rooms, kitchen or mechanical rooms.
- Verify that A/C system is operable, if not, repair, replace or remove and seal all openings.
- Mechanical gas permit is required for the above work.

As owner, agent or responsible party, you are hereby notified that if these deficiencies and the resulting nuisance condition is not corrected by **July 26, 2017** the Department of Safety and Inspections, Division of Code Enforcement, will begin a substantial abatement process to demolish and remove the building(s). The costs of this action, including administrative costs and demolition costs will be assessed against the property taxes as a special assessment in accordance with law.

As first remedial action, a Code Compliance Inspection Report must be obtained from the Building Inspection and Design Section, 375 Jackson Street, Suite 220, (651) 266-8989. This inspection will identify specific defects, necessary repairs and legal requirements to correct this nuisance condition. You may also be required to post a five thousand dollar (\$5,000.00) performance bond with the Department of Safety and Inspections before any permits are issued, except for a demolition permit. Call the Department of Safety and Inspections for more information at 651-266-8989.

If this building is located in a historic district or site (noted on page 1, above, just below the property address) then you must contact Heritage Preservation (HPC) staff to discuss your proposal for the repairs required by this order and compliance with preservation guidelines. Copies of the guidelines and design review application and forms are available from the Department of Safety and Inspections web site (see letterhead) and from the HPC staff. No permits will be issued without HPC review and approval. HPC staff also can be reached by calling 651-266-9078.

June 26, 2018 993 JAMES AVE Page 5

As an owner or responsible party, you are required by law to provide full and complete disclosure of this "Order to Abate" to all interested parties, all present or subsequent renters and any subsequent owners. The property shall not be sold, transferred or conveyed in any manner until the Nuisance Conditions have been abated and the Certificate of Code Compliance or Certificate of Occupancy has been issued.

The Enforcement Officer is required by law to post a placard on this property which declares it to be a "nuisance condition", subject to demolition and removal by the City. This placard shall not be removed without the written authority of the Department of Safety and Inspections, Division of Code Enforcement. The department is further required to file a copy of this "Order to Abate" with the City Clerk's Office.

If corrective action is not taken within the time specified in this order, the Enforcement Officer will notify the City Council that abatement action is necessary. The City Clerk will then schedule dates for Public Hearings before the City Council at which time testimony will be heard from interested parties. After this hearing the City Council will adopt a resolution stating what action if any, it deems appropriate.

If the resolution calls for abatement action the Council may either order the City to take the abatement action or fix a time within which this nuisance must be abated in accordance with the provisions of Chapter 33 of the Saint Paul Legislative Code and provide that if corrective action is not taken within the specified time, the City shall abate this nuisance. The costs of this action, including administrative costs will be assessed against the property as a special assessment in accordance with law.

If you have any questions or request additional information please contact **Matt Dornfeld** at **651-266-1902**, or you may leave a voice mail message.

Sincerely,

Matt Dornfeld Vacant Buildings Enforcement Inspector

cc: Legistar Approval list and City Council